



**NOTES:**

1. DIMENSIONS ARE IN MILLIMETERS [INCHES].

**STANDARD SPECIFICATIONS & COMMON OPTIONS (HOW TO ORDER)**

- STD. SCREW MATERIAL: TYPE 18/8 STAINLESS STEEL PER DFARS (OTHER MATERIALS AVAILABLE)
- STD. SCREW FINISH: PASSIVATED PER AMS2700 (UNLESS OTHERWISE SPECIFIED)
- STD. O-RING MATERIAL: SILICONE RUBBER (SEE TABLE FOR O-RING OPTIONS)

SAMPLE CATALOG NO.		HPM6X12MM-2701-BLKOX	COMMON OPTIONS		AVAILABLE O-RING MATERIALS		
O-RING SUFFIX	-2701	ENTER FROM TABLE	SUFFIX	DESCRIPTION	Compound Suffix	Material	Service Temp.
OPTIONS	-BLKOX	ENTER FROM TABLE	-BLKOX	BLACK OXIDE PER MIL-C-13924, CLASS 4	-2701	Silicone Rubber	-150° F to 500° F -101° C to 260° C
<b>RECOMMENDED CLEARANCE HOLE DETAIL</b> 			-NY	LOCKING NYLON PELLET	-2615	FluoroSilicone Rubber	-78° F to 450° F -61° C to 232° C
			-LY	LOCKING NYLON STRIP	-5701	Viton A	-20° F to 400° F -29° C to 204° C
			-TP	LOCKING NYLON STD. PATCH	-4601	Buna N (NBR)	-65° F to 250° F -54° C to 121° C
			-HTP	HIGH TEMP. LOCKING NYLON PATCH	-3701	Neoprene (EPR)	-65° F to 300° F -54° C to 149° C
					-7601	Ethylene Propylene (EPDM)	-65° F to 300° F -54° C to 149° C

A	ECO-18-0008: CHANGED PIN DIA FROM 1.37 [0.054] TO 1.93 [0.076]. DWN: DAN LAW CHKD: KF/FK/SM/JC 05.07.18	04.23.18
REV.	DESCRIPTION	DATE

<b>TOLERANCES UNLESS OTHERWISE NOTED</b> .X ±0.1 .XXX ±0.005 .XX ±0.01 < ±1.0° <b>RUBBER: RMA "A3" COMMERCIAL</b>	<b>TITLE:</b> <b>SEELSKREW®, METRIC PANHEAD w/ HEX SECURITY DRIVE</b>
<b>MAT'L:</b> <b>SEE SPECIFICATIONS &amp; OPTIONS</b>	
<b>FINISH:</b> <b>SEE SPECIFICATIONS &amp; OPTIONS</b>	

**ALCYON**  
ÉLECTRONIQUE

Tel : +33 (0) 1 34 94 77 00  
<https://alcyonelectronique.fr/>