SPECIFICATIONS

Elastomer: Silicone conforms to A-A-59588, Class 3A, GR60, Gray (unless otherwise specified).
Mounting Nut: Brass, nickel-plated (unless otherwise specified).
RFI Mesh: Monel per QQ-N-281, Class A
Temperature Range: -75° C to + 204° C (-103° F to + 400° F)
Operational Life: 50,000 actuations (minimum).
Shelf Life: Excess of 25 years.
Resistant to: Splash, salt spray, sunlight, ozone, weather, fungus, dust, and most acids and lubricating oils.
Agency Recognition: UL & ULC Recognized to UL Std. 50.







SECTION A-A



NOTES:

1. REACH, RoHS, PROP 65 DECLARATIONS.

REV.	DESCRIPTION	DATE

TOLERANCES UNLESS OTHERWISE NOTED
.X ± 0.25 .XXX ±0.013
.XX ±0.13 ∠ ±1.0°
FOR RUBBER PORTION ONLY:
RMA "A3" COMMERCIAL
DIMENSIONS ARE IN MILLIMETERS [INCHES]

MATERIAL & FINISH:
SEE SPECIFICATIONS

TITLE:
SEAL, ROTARY
w/ EMI/RFI SHIELD, 6MM SHAFT

ENG.	LP	02.16.22
DWN.	DAN LAW	02.16.22
CHKD.	SHM/LP	02.16.22

APM HEXSEAL Sealing Specialists

SCALE	DWG. NO.
5.000	1332/46 RFI

THIS DRAWING IS THE PROPERTY OF APM HEXSEAL CORPORATION AND INCLUDES PROPRIETARY INFORMATION.
THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE WRITTEN APPROVAL OF AN OFFICER OF APM HEXSEAL CORPORATION.