



COMBOSENSE™ 6024 SERIES

Temperature Sensor & Thermostat Probe

Introduction

The Airpax™ 6024 thermal sensor-switch offers the function and reliability of a grounded case snap-action thermostat with the sensing capability of a solid-state thermistor in a single economical package. The switch is available in temperature ranges from 40°C to 130°C, with a variety of terminal and body options.

The 6024 series is ideal for sensing engine oil / coolant or transmission fluid for overheat conditions. Additionally, it provides a solution for engine applications where mounting holes are limited.



Features

- Thermostat & temperature sensor in one robust package
- Stainless steel or brass construction
- Ideal for immersion sensing where mounting holes are limited



SPECIFICATIONS

Contact Ratings	<i>Cycles</i> 30,000	<i>Voltage</i> 120VAC / 48VDC	<i>Amps</i> 1 (resistive)
Contact Operations	Either close on rise (make) or open on rise (break), SPST (Single Pole, Single Throw)		
Operating Temperature	40°C to 130°C (104°F to 266°F), std tolerance ±5°C (±8°F)		
Dielectric Strength	500 VAC, 60Hz thermostat terminals to case across open contacts <i>Note: Do not apply dielectric test voltage to the thermistor terminal as permanent damage could occur to the sensor element</i>		
Insulation Resistance	50 megaohms, minimum at 500 VDC		
Vibration	.06DA, 10-55 Hz, 20G 10-2000 Hz		
Shock	75G 6ms duration (sawtooth)		
Materials	Stainless steel or brass body and tube, Mylar sleeve, epoxy fill potting, stainless or plated steel terminals, fine silver contacts, gold-plated crossbar for low level switching		



TEMPERATURE SENSOR SPECIFICATIONS

Solid-State Sensor	Conventional NTC (Negative Temperature Coefficient) and PTC (Positive Temperature Coefficient) thermistors available. Specific resistance values and tolerances are per customer specifications.
Operating Temperature	-40°C to 120°C (-40°F to 248°F) (other ranges available)



THERMOSTAT TEMPERATURE SETPOINTS

OPERATE ($\pm 5^{\circ}\text{C}$)	MIN DIFFERENTIAL ($^{\circ}\text{C}$)	MIN RESET ($^{\circ}\text{C}$)
40	4	20
45	4	20
50	4	30
55	4	30
60	4	40
65	4	40
70	4	50
75	4	50
80	6	55
85	6	55
90	6	60
95	6	60
100	6	70
105	6	70
110	6	80
115	6	80
120	9	85
125	9	85
130	9	90



ORDERING OPTIONS

Example : C6024CBA-5555

Close contacts on temperature rise, 5100 series, isolated case 6" flying leads, 1/2-14 PTF threads, .698" tube length. Non-descript assigned for thermostat temperature and thermistor selection.

Contact Operation C **6024** C B A - 5 5 5 5

O = Open on Rise
C = Close on Rise

Basic Product Series **6024**

Terminal Selection **A-F** = Reference Table 1
Z = Special Requirements, Customer to Specify

Mounting Thread Selection **A-D** = Reference Table 2
Z = Special Requirements, Customer to Specify

Tube Length Selection **A-B** = Reference Table 3
Z = Special Requirements, Customer to Specify

Non-Descript from Sensata

Non-descript assigned for thermostat temperature and thermistor selection.



TABLES

TABLE 1: TERMINAL SELECTION		
<p>A</p>	<p>B</p>	<p>C</p>
<p>D Same as terminal selection "C"</p> <p>Except 2 Leads $\frac{(304.80 \pm 25.40)}{12.00 \pm 1.00}$</p> <p>See note 1 for lead specifications</p>	<p>E Same as terminal selection "C"</p> <p>Except 2 Leads $\frac{(609.60 \pm 25.40)}{24.00 \pm 1.00}$</p> <p>See note 1 for lead specifications</p>	<p>F Same as terminal selection "C"</p> <p>Except 2 Leads $\frac{(1219.20 \pm 25.40)}{48.00 \pm 1.00}$</p> <p>See note 1 for lead specifications</p>

- The standard lead wire (materials) for different temperature ranges are as follows:
 - Up to 220°F (104.4°C) = # 18 AWG stranded. UL Style 1015/CSA approved. (PVC insulation, color black)
 - 221°F to 350°F (105°C to 176.6°C) = #18 AWG stranded. UL Style 1199/CSA approved. (Teflon® TFE insulation, color black)

TABLE 3: TUBE LENGTH SELECTION	
<p>A</p>	<p>B</p>

TABLE 2: MOUNTING THREAD SELECTION	
<p>A</p>	<p>B</p>
<p>C</p>	<p>D</p>

Revised 3/9/18

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

Copyright © 2018 Sensata Technologies, Inc.

CONTACT US

Americas

+1 (888) 438 2214

sensors@sensata.com

Europe, Middle East & Africa

+31 (74) 357 8156

temperature-info.eu@sensata.com

com

Asia Pacific

sales.isasia@list.sensata.com

China +86 (21) 2306 1500

Japan +81 (45) 277 7117

Korea +82 (31) 601 2004

India +91 (80) 67920890

Rest of Asia +886 (2) 27602006

ext 2808

www.sensata.com